



# MASTERFLEX<sup>®</sup>

## TYGON<sup>®</sup> E-LAB (E-3603) PUMP TUBING

THE NEXT GENERATION OF THE MOST POPULAR  
TUBING WITH RESEARCHERS WORLDWIDE

**NEW**

- **No BPA or phthalates**—environmentally responsible, more sustainable, and safer for products, people, and the planet
- **Non-DEHP tubing features a bio-based plasticizer** for a lower global impact
- **Formulated for longer life in peristaltic pumps**—outlasts most competitors by 3 to 1
- **Economically priced** for general transfer applications
- **Crystal clear** for easy flow monitoring
- **Noncontaminating** and nonoxidizing
- **Compatible** with virtually all inorganic chemicals
- **Meets USP Class VI, FDA, and NSF 51 criteria\***
- **Available in most Masterflex<sup>®</sup> sizes** to ensure the best performance when used with Masterflex peristaltic pumps

\*Contact Cole-Parmer for a validation binder with up-to-date test results and compliance certificates.

 **Cole-Parmer**<sup>®</sup>  
Delivering Solutions You Trust

## In the US

625 E. Bunker Court  
 Vernon Hills, IL 60061  
 Call toll-free 800-323-4340  
 Phone: 847-549-7600  
 Fax: 847-247-2929  
[www.coleparmer.com](http://www.coleparmer.com)

## In Canada

Call toll-free 800-363-5900  
 Phone: 514-355-6100  
 Fax: 514-355-7119  
[www.coleparmer.ca](http://www.coleparmer.ca)

## In India

Phone: 91-22-6716-2222  
 Fax: 91-22-6716-2211  
[www.coleparmer.in](http://www.coleparmer.in)

## In the United Kingdom

Free phone: 0500-345-300  
 Phone: 020-8574-7556  
 Fax: 020-8574-7543  
[www.coleparmer.co.uk](http://www.coleparmer.co.uk)

## International customers

Call 847-549-7600 to reach our  
 International Sales Department  
 or contact your local dealer.



**FREE TECHNICAL  
 APPLICATIONS ASSISTANCE!**

## APPLICATIONS

- General laboratory
- Analytical instruments
- Transfer of viscous fluids

## PERFORMANCE SPECIFICATIONS

- Temperature range  
 Static: -50 to 74°C (-58 to 165°F)  
 Dynamic (pumping): 0 to 40°C (32 to 105°F)
- Sterilize by EtO or autoclave at 121°C (250°F)
- RoHS compliant
- REACH compliant



Catalog number	Tubing size	Hose barb	Quantity/pk
<b>L/S® Precision pump tubing</b>			
<a href="#">MK-06509-13</a>	L/S 13	1.6 mm (1/16")	15.2 m (50 ft)
<a href="#">MK-06509-14</a>	L/S 14	1.6 mm (1/16")	
<a href="#">MK-06509-16</a>	L/S 16	3.2 mm (1/8")	
<a href="#">MK-06509-25</a>	L/S 25	4.8 mm (3/16")	15.2 m (50 ft)
<a href="#">MK-06509-17</a>	L/S 17	6.4 mm (1/4")	
<a href="#">MK-06509-18</a>	L/S 18	9.5 mm (3/8")	
<b>L/S® High-Performance Precision pump tubing</b>			
<a href="#">MK-06509-15</a>	L/S 15	4.8 mm (3/16")	15.2 m (50 ft)
<a href="#">MK-06509-24</a>	L/S 24	6.4 mm (1/4")	
<a href="#">MK-06509-35</a>	L/S 35	9.5 mm (3/8")	
<a href="#">MK-06509-36</a>	L/S 36	9.5 mm (3/8")	
<b>I/P® Precision pump tubing</b>			
<a href="#">MK-06509-26</a>	I/P 26	9.5 mm (3/8")	15.2 m (50 ft)
<a href="#">MK-06509-73</a>	I/P 73	6.4 mm (1/4")	
<a href="#">MK-06509-82</a>	I/P 82	9.5 mm (3/8")	
<b>I/P® High-Performance Precision pump tubing</b>			
<a href="#">MK-06509-70</a>	I/P 70	9.5 mm (3/8")	15.2 m (50 ft)
<a href="#">MK-06509-88</a>	I/P 88	12.7 mm (1/2")	
<a href="#">MK-06509-89</a>	I/P 89	15.88 mm (5/8")	